Print / Save as PDF



E-Pro Surface

E-Pro Surface Mounted 16W 2x2 Cells White Finish 3000K

PRODUCT DATA

Part Code (s)	**R093622/WT/3K/16W**
Applications	**Interior**
Warranty	5 years
Certification(s)	CE, RoHS, UKCA


PHYSICAL DATA


Colour Finish	Matte White (RAL9016)
Body Colour	White
Dimensions (mm)	86 x 86 x H88mm
Luminaire Fixing	**Surface Mounted**
Construction Material	Aluminium
Diffuser Type	Polycarbonate TPa Rated (Round Aperture)


ELECTRICAL DATA

Wattage	16W
Voltage Range	AC200-240V
Power Factor	>0.90
Inrush Current	<10A
Running Current	400mA

DIMENSION DIAGRAM


86mm
86mm


88mm


Ø25mm

Part Code: R093622/WT/3K/16W

TECHNICAL DATA

Lumens (±5%)	1580
Efficacy	~99 Lm/W
Operating Temperature	-20°C to +45°C
Beam Angle	50°
Operating Hours	>50000
IP Rating	IP20
IK Rating	IK07

LIGHT SOURCE DATA

Kelvins	**3000K**
CRI	>90Ra
Macadam Ellipse	equal or less than 3 sdcm
L80 B50	**90000 hours**
LEDs	CREE 5050

PHOTOMETRIC DIAGRAM

Image not available