Print / Save as PDF



E-Pro Surface

E-Pro Surface Mounted 36W 3x3 Cells White Finish 4000K

PRODUCT DATA

Part Code (s)	**R093633/WT/4K/36W**
Applications	**Interior**
Warranty	5 years
Certification(s)	CE, RoHS, UKCA


PHYSICAL DATA

Colour Finish	Matte White (RAL9016)
Body Colour	White
Dimensions (mm)	125 x 125 x 88mm
Luminaire Fixing	**Surface Mounted**
Construction Material	Aluminium
Diffuser Type	Polycarbonate TPa Rated (Round Aperture)

ELECTRICAL DATA

Wattage	36W
Voltage Range	AC200-240V
Power Factor	>0.90
Inrush Current	<10A
Running Current	800mA

DIMENSION DIAGRAM


125mm
125mm
88mm
Ø25mm

Part Code: R093633/WT/4K/36W

TECHNICAL DATA

Lumens (±5%)	3755
Efficacy	~105 Lm/W
Operating Temperature	-20°C to +45°C
Beam Angle	50°
Operating Hours	>50000
IP Rating	IP20
IK Rating	IK07

LIGHT SOURCE DATA

Kelvins	**4000K**
CRI	>90Ra
Macadam Ellipse	equal or less than 3 sdcm
L80 B50	**90000 hours**
LEDs	CREE 5050

PHOTOMETRIC DIAGRAM

Image not available